





S4 / BNB Solder Tag



S4 / BNB PC - A



S4 / BNB PC - C



S4 / BBB PC - C Kinked

The **CLIFF®** range of S4 Jack Sockets incorporate our Ni-Ag® Alloy Self-Cleaning Contacts for superior performance and reliability. All models have a durable premium quality nylon body. The S4 Jack Socket is available in mono or stereo with unswitched, switched or make contacts and with a choice of either solder tag or six standard PCB mounting versions.

Significant features include:

- Ni-Ag® Alloy Self-Cleaning Contacts for superior performance and reliability.
- Optional 'Kinked' Legs for snap-in PCB mounting on PC-A and PC-C styles to facilitate pre-assembly and wave soldering.
- Tough, molded Nylon body.
- Optional Chassis Grounding versions.
- Optional Plated Contacts.
- Optional EMI/RFI Screen.
- Optional combined Nut to Bezel.

Cliff Electronic Components, Ltd.

76 Holmethorpe Avenue, Holmethorpe Ind. Est.

Redhill, Surrey RH1 2PF, England

Tel: +44 (0) 1737 771375


Fax: +44 (0) 1737 766012

Email: sales@cliffuk.co.uk




Visit us online at:

www.cliffuk.co.uk



BACK OF SOCKET		FRONT OF SOCKET		
<p>SPECIAL REVERSED CUT CONTACT</p> <p>12.5 TO C/L</p> <p>(12.5 = SPECIAL)</p>	<p>PC TYPE A/S</p>	<p>PC TYPE A</p>	<p>PC TYPE B</p>	<p>PC TYPE C</p>
<p>PCA/S/REV</p>	<p>PC-C 'KINKED'</p>	<p>PC TYPE D</p>	<p>PC TYPE E</p>	

Printed Circuit Board Styles



OPTION
S4P HAS COMBINED NUT & BEZEL MADE FROM PLASTIC MATT BLACK FINISH.

Specification:

Withstand voltage: 2000V DC Min.
Maximum Current: 5 amps
Temperature Rating: -10° C to +70° C
Life (Minimum): 10,000+ Operations
Nominal Contact Resistance: <50mΩ

Technical Data:

Designed to receive both mono and stereo 1/4" jack plugs, the S4 socket is produced from grade 1 black nylon and is supplied with a high quality Chrome plated Brass nut. Mounting is effected by screwing the Chrome Facia nut (with plastic bezel) into a threaded plastic bush which protrudes from the body. Coloured bezels are also available for identification purposes. For superior performance, the contacts are **CLIFF®** Ni-Ag® Alloy and are designed to self-clean upon insertion and removal of the jack plug. The contacts can also be supplied with our special low noise Ni-Ag® 'ST' or Gold plating and in addition to the standard solder tag version, there are six standard PCB mounting styles available. The S4 can also be supplied with prefitted EMI/RFI screen if required. When ordering, please state the contact arrangement required, with a plug inserted, using the following code from the front of the jack socket: B - Break, M - Make, S - Single, N - No Contact. For example, an S4/BMB PC-C Black is a 3-pole stereo jack socket, 1st contact - 'Break', 2nd contact - 'Make' and third contact - 'Break' with PC-C solder pins.



S4 Coloured Bezels



S4 Combined Nut & Bezel



S4 EMI/RFI Screen



S2 / BNB Solder Tag



S2 / BBB PC - A Special Nose



S2 / BNB PC - C Kinked



S2 / BBB PC - C Kinked

The **CLIFF®** range of S2 Jack Sockets incorporates our Ni-Ag® Alloy Self-Cleaning Contacts for superior performance and reliability. All models have a durable premium quality nylon body. Mounting hardware is normally supplied unassembled. The S2 Jack Socket is available with optional chassis grounding in mono or stereo with unswitched, switched or make contacts and with a choice of either solder tag or six standard PCB mounting versions.

Significant features include:

- Ni-Ag® Alloy Self-Cleaning Contacts for superior performance and reliability.
- Optional 'Kinked' Legs for snap-in PCB mounting on PC-A and PC-C styles to facilitate pre-assembly and wave soldering.
- Tough, molded Nylon body. Standard colour black.
- Optional Chassis Grounding versions.
- Optional Plated Contacts.
- Optional EMI/RFI Screen.

Cliff Electronic Components, Ltd.

76 Holmethorpe Avenue, Holmethorpe Ind. Est.

Redhill, Surrey RH1 2PF. England

Tel: +44 (0) 1737 771375

Fax: +44 (0) 1737 766012


Email: sales@cliffuk.co.uk



Visit us online at:

www.cliffuk.co.uk

1/4" S2 Mono & Stereo Jack Sockets



Specification:

Withstand voltage: 2000V DC Min.
Maximum Current: 5 amps
Temperature Rating: -10° C to +70° C
Life (Minimum): 10,000+ Operations
Nominal Contact Resistance: <50mΩ

Technical Data:

Designed to receive both mono and stereo 1/4" jack plugs, the S2 socket is produced from grade 1 black nylon and is supplied with a black nylon hexagonal mounting nut (standard) or optional nickel plated brass hexagonal nut or slotted ring nut. Coloured nylon nuts are also available for identification purposes. Contacts can be supplied with our special low noise Ni-Ag® 'ST' or Gold plating and in addition to the standard solder tag version, there are six different PCB mounting styles available. The S2 can also be supplied with prefitted EMI/RFI screen if required. When ordering, please state the contact arrangement required, with a plug inserted, using the following code from the front of the jack socket: B - Break, M - Make, S - Single, N - No Contact. For example, an S2/BMB PC Mounting type C Black, is a PC-C 3-pole stereo jack socket, 1st contact - 'Break', 2nd contact - 'Make' and third contact - 'Break'.



S2 Coloured Nut



S2 Hex Chrome Nut



Slotted Ring Nut



S2 EMI/RFI Screen