

Spiral shielded cables



RoHS
Conformity

Applications:
Flexible cable for sound reproduction and electronics.

Characteristics:
Conductor: O.F.C. red copper
Cond. Insulation: PVC
Core colour: Red
Shield: Spiral covering 100% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



Conductor Resistance	Capacity Core/core	Capacity Core/shield
$\Omega/\text{Km} \pm 5\%$	pF/mt	pF/mt
75		460
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

RoHS
Conformity

Applications:
Flexible cable for sound reproduction and electronics.

Characteristics:
Conductor: O.F.C. red copper
Cond. Insulation: Compact PE
Core colour: White
Shield: Spiral covering 100% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



75		94
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

RoHS
Conformity

Applications:
Flexible cables with individually shielded cores for sound reproduction and electronics.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: PVC
Core colours: Black, White, Red, Yellow, Green
Shields: Spiral covering 100% O.F.C. red copper
Sheath: PVC
Sheath colour: Black



130	150	290
130	150	290
130	150	370
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

tasker®
Code

Cond.
number

Nominal
section
mm²

Cond. Format.
mm.

External
Core
Ø mm.

External
Cable
Diameter
mm.

Reel or Spool
(* pag. II)

mt.

Type

Kg.

C113

1

1 x 0,25
(23 AWG)

8x0,20

1,5

3,0

200

B

3,0

C123

1

1 x 0,25
(23 AWG)

8x0,20

2,3

4,5

100

B

2,8

C115

3

3 x 0,14
(26 AWG)

18x0,10

1,3

5,0

100

B

4,0

C116

4

4 x 0,14
(26 AWG)

18x0,10

1,3

5,2

100

B

4,2

C181

5

5 x 0,14
(26 AWG)

18x0,10

1,3

6,5

100

B

6,5