


Dimensional Outline and Pin Connection inch(mm)



Features: Compact moisture resistant package

Lowest "on" resistance

Low distortion

Ideal for Hi-Fi stereo applications

Storage Temperature: -30 to +80°C

Operating Temperature: -30 to +80°C

Soldering Temperature: 260°C <10s

Isolation Voltage(peak): 2000V

Output Resistance vs. Forward Current


Symbol	Parameter	Min	Typ	Max	Units	Test Conditions
LED						
I_F	Forward Current			40	mA	(Derate Linearly to 0 at 75°C)
V_F	Forward Voltage			2.0	V	I _F = 16 mA
I_R	Reverse Current			100	μA	V _R =3.8V
Cell						
V_C	Maximum Cell Voltage			60	V	(Peak AC or DC)
P_D	Power Dissipation			50	mW	(Derate Linearly to 0 at 75°C)
Coupled						
R_{ON}	On Resistance					
		40		80	KΩ	I _F = 0.5 mA**
				6.0	KΩ	I _F = 5 mA**
R_{OFF}	Off Resistance		400		KΩ	10sec after I=0.3Vdc on cell
T_R	Rise Time			3.5	msec	Time to 63% of final conductance @ I _F = 16 mA ***
T_F	Decay Time		50		msec	Time to 1MΩ after removal of input @ I _F = 16 mA
	Cell Temp Coefficient		1.0		%°C	I _F >5 mA

* 2mm from case for < 5 sec


* * measured after a dark history of 1 week

* * * Rise time is the time for the dark change in conductance to reach 63% of its final value


Output Resistance vs. Forward Current



Rise/Fall Time vs. Load Resistance



LED Forward Current vs. Forward Voltage



规格书各项参数仅供使用参考
用户标准以样品为准